



Firmware for EDR-G9004 Series Release Notes

Version: v3.13	Build: 24100800
Release Date: Oct 09, 2024	

Applicable Products

N/A

Supported Operating Systems

N/A

New Features

- Added a CPU usage notification to Event Notification.
- Added a port usage notification to Event Notification.
- Added support for new DPI protocols to Advanced Protection: Step7 Comm+, OPC UA, MELSEC.
- Added support for RFC 5424 formatted syslog messages.
- Added a Default Action Log to Layer 3-7 Policy.
- Added support for 2.5G SFP modules.

Enhancements

- Added Syslog as a Registered Action for the VRRP State Changes event notification.
- Added syslog as a Registered Action for the Fiber Check Warnings event notification.
- Error logs for failed configuration imports now show more details.
- Users can now select multiple inbound interfaces for Static Multicast Routes within same group address.
- Added error logs for the DHCP function.
- Added error logs for the IGMP function.
- Added support for Modbus DPI protocols in the CLI.

Bugs Fixed

- The port-based DHCP server incorrectly assigns duplicate IP addresses to bridge ports.
- RSTP incorrectly assigns multiple devices as the root.
- Users are only able to configure or import one Static Multicast entry through the CLI.
- SNMP OIDs including the "newline" character returns an error.
- Importing configurations containing SNTP/NTP server or SNTP client settings results in an error.
- The NAT function does not work properly after rebooting the device.
- The PRP traffic function for MTU configuration does not work properly.
- The firewall pop-up window remains visible after the system automatically logs out.
- IEEE 802.1X authentication for the RADIUS server would fail.
- Vulnerability: CVE-2024-9137
- Vulnerability: CVE-2024-9139
- Vulnerability: CVE-2024-1086
- The connection status of the OpenVPN Client function shows incorrectly.

Changes

- Increased the maximum password and share key length to 64 characters for user accounts, IPsec, L2TP server, SNMP, IEEE 802.1X, RADIUS server, and TACACS+ server.
- Added support for special characters in passwords and shared keys for user accounts, IPsec, L2TP server, SNMP, IEEE 802.1X, RADIUS server, and TACACS+ server.

Notes

N/A



Version: v3.12.1	Build: 24082116
Release Date: Aug 26, 2024	

Applicable Products

N/A

Supported Operating Systems

N/A

New Features

N/A

Enhancements

N/A

Bugs Fixed

- Unsupported or unavailable features appear in the web interface.

Changes

N/A

Notes

N/A



Version: v3.12	Build: 24073101
Release Date: Aug 02, 2024	

Applicable Products

N/A

Supported Operating Systems

N/A

New Features

- Added support for the Loopback Interface function.
- Added support for the OpenVPN Client function.
- Added support for the Netflow function.
- Added support for event-triggered actions to the VRRP function.
- Added support for UDP-Flood to the DoS Policy function.
- Added SNMP Trap as a Log Destination for the Layer 2 Policy function.
- Added support for additional event log export formats: .pdf, .csv.

Enhancements

- Enhanced the following IPsec algorithms.
 - Encryption: AES-256-GCM
 - Hash: SHA-512
 - DH Group: DH15 (modp3072), DH16 (modp4096), DH17 (modp6144), DH18 (modp8192), DH22 (modp1024s160), DH23 (modp2048s224), DH24 (modp2048s256), DH31 (curve25519)
 - PRF: PRF SHA-256, PRF SHA-384, PRF SHA-512

Bugs Fixed

- The "Login Authentication Failure Message" does not save properly.
- Using the newline character (\n) in the 'Login Message' and 'Login Authentication Failure Message' causes abnormalities in the output.
- The system is unable to ping the VRRP virtual IP.
- Users are able to bypass password policy violation warnings by pressing ESC on the keyboard.
- Time zone settings are not saved if GMT is set to 0.
- Vulnerability: CVE-2024-6387.

Changes

- Changed the IPS license expiration behavior: When the license expires, IPS functionality will now remain enabled, but the IPS patterns will no longer be updated.
- Changed the Trusted Access behavior: Trusted Access now applies to the Web UI, CLI, and New Moxa Command interfaces.
- Changed the Preempt Delay range for the VRRP function from 10 to 300 to 0 to 300

Notes

N/A



Version: v3.10	Build: 24070315
Release Date: Jul 26, 2024	

Applicable Products

N/A

Supported Operating Systems

N/A

New Features

First release.

Enhancements

N/A

Bugs Fixed

N/A

Changes

N/A

Notes

N/A