



## Firmware for ioLogik E1200 Series (E1212) Release Notes

<b>Version: v3.2</b>	<b>Build: Build20111915</b>
<b>Release Date: Dec 25, 2020</b>	

### Applicable Products

ioLogik E1212, ioLogik E1212-T

### Supported Operating Systems

N/A

### New Features

- Safe Mode supports Ethernet/IP protocol.

### Enhancements

N/A

### Bugs Fixed

- DHCP mode will not get the Gateway IP.
- The counter value is reset after power failure when booting up.
- The serial number is displayed incorrectly on the web console.
- Ethernet/IP implicit messages are sent to port 2222 by default.

### Changes

N/A

### Notes

N/A



<b>Version: v3.1</b>	<b>Build: Build19110615</b>
<b>Release Date: Nov 26, 2019</b>	

### **Applicable Products**

ioLogik E1212, ioLogik E1212-T

### **Supported Operating Systems**

N/A

### **New Features**

- EtherNet/IP registration on Moxa's licensing website is no longer required.
- Added case insensitive content-length for RESTful API.

### **Enhancements**

N/A

### **Bugs Fixed**

- Fixed inaccurate counter value when using Modbus to start a pulse (E1210/E1212/E1213).
- Fixed opposite on/off pulse width display on web console (E1211/E1212/E1214).
- Fixed that the offset scaling value will reset after changing the Alias name (E1260).
- Fixed self-rebooting when entering URL in the browser for the configuration file.
- Fixed EDS file import connection error.
- Fixed failure when using save counter on power failure and reset counter at the same time (E1210/E1212/E1213).
- Fixed inaccurate counter value when using high frequency (E1210/E1212/E1213).
- Fixed that the trap community name is not included in the export file.
- Fixed that EtherNet/IP cannot use the "Set Attribute Single" service.
- Added an enable RESTful API setting in the configuration file.

### **Changes**

N/A

### **Notes**

N/A



<b>Version: v3.0</b>	<b>Build: Build17111512</b>
<b>Release Date: Jan 16, 2018</b>	

### **Applicable Products**

ioLogik E1212-T, ioLogik E1212

### **Supported Operating Systems**

N/A

### **New Features**

- Added OPTIONS method for RESTful API.
- Added quick access URI for RESTful API.

### **Enhancements**

- Added SNMP Trap Community Setting on web console.
- Mentioned max. 16 characters on password setting page.

### **Bugs Fixed**

- Fixed DHCP lease time did not ask for extension when half of the lease time elapsed.
- Closed IP forwarding function (Port 0).
- Closed UDP Port 161 when SNMP agent is disabled.
- Fixed RESTful API header case-sensitive issue.
- Fixed invalid token issue on login page when using Firefox.

### **Changes**

N/A

### **Notes**

- This version of firmware works with the ioSearch V2.0 or later only.
- Update only the next or the previous released firmware version to prevent from system failure.



<b>Version: v2.5</b>	<b>Build: Build16091211</b>
<b>Release Date: N/A</b>	

### **Applicable Products**

ioLogik E1212, ioLogik E1212-T

### **Supported Operating Systems**

N/A

### **New Features**

- Added EtherNet/IP protocol.
- Added RESTful API.
- Added new registers for Modbus/TCP protocol.
- Added new OIDs of SNMP protocol.
- Modbus, EtherNet/IP, RESTful Services can be disabled (default: enable).
- Added sending heartbeat to 9500 port of MX-AOPC UA Server after heartbeat function is enabled.
- Increased password length from 8 to 16.
- Added checking special character function for preventing from Cross-Site Scripting.
- Changed sending password from GET to POST method.

### **Enhancements**

N/A

### **Bugs Fixed**

- Fixed file transfer with Chrome browser issue (e.g. firmware update, configuration import or export).

### **Changes**

N/A

### **Notes**

N/A



<b>Version: v2.4</b>	<b>Build: Build16053018</b>
<b>Release Date: N/A</b>	

**Applicable Products**

ioLogik E1212, ioLogik E1212-T

**Supported Operating Systems**

N/A

**New Features**

- Improved protocol efficiency with ioLogik 2500 series.

**Enhancements**

N/A

**Bugs Fixed**

N/A

**Changes**

N/A

**Notes**

N/A



<b>Version: v2.3</b>	<b>Build: Build15031013</b>
<b>Release Date: N/A</b>	

### **Applicable Products**

ioLogik E1212-T, ioLogik E1212

### **Supported Operating Systems**

N/A

### **New Features**

- Supports ioLogik 2500 expansion mode.
- Supports safe mode auto-clear function.
- Supports counter initial value function.
- Supports DO Power ON Delay function.

### **Enhancements**

N/A

### **Bugs Fixed**

- Unable to disable the P2P Heart beat interval.
- When the Heart beat Interval Time = 0, the P2P server will reconnect continuously.
- When the P2P client heartbeat is set to a value larger than 256, the time interval will be incorrect.
- When one DI channel mapping to multiple DO channels in P2P mode, the update interval will be fixed.

### **Changes**

N/A

### **Notes**

N/A



<b>Version: v2.0</b>	<b>Build: Build13041515</b>
<b>Release Date: N/A</b>	

### **Applicable Products**

ioLogik E1212, ioLogik E1212-T

### **Supported Operating Systems**

N/A

### **New Features**

- Supports SNMP protocol.
- Add P2P heartbeat function .

### **Enhancements**

N/A

### **Bugs Fixed**

- When power failing, counter storage fail.

### **Changes**

N/A

### **Notes**

- This version of firmware works with the ioSearch V1.5 or later only.
- Use web console when upgrading firmware from V1.0 to V1.10.



<b>Version: v1.10</b>	<b>Build: Build12010416</b>
<b>Release Date: N/A</b>	

**Applicable Products**

ioLogik E1212, ioLogik E1212-T

**Supported Operating Systems**

N/A

**New Features**

N/A

**Enhancements**

- Wording change for DO pulse output .

**Bugs Fixed**

N/A

**Changes**

N/A

**Notes**

N/A





<b>Version: v1.9</b>	<b>Build: Build11112413</b>
<b>Release Date: N/A</b>	

**Applicable Products**

ioLogik E1212, ioLogik E1212-T

**Supported Operating Systems**

N/A

**New Features**

N/A

**Enhancements**

- Ensured system to work properly after unstable power condition.

**Bugs Fixed**

N/A

**Changes**

N/A

**Notes**

N/A



<b>Version: v1.8</b>	<b>Build: Build11092917</b>
<b>Release Date: N/A</b>	

### **Applicable Products**

ioLogik E1212, ioLogik E1212-T

### **Supported Operating Systems**

N/A

### **New Features**

- Added Locating I/O function in General Settings.
- Added Modbus address function code=0x08 for “ECHO” function.
- Counter overflow status is displayed on Channel Settings, and can be manually cleared.
- Added Modbus address for Peer-to-peer connection and safe mode status.
- Peer-to-peer connection and safe mode status are displayed on Channels Safe Mode Settings.

### **Enhancements**

N/A

### **Bugs Fixed**

N/A

### **Changes**

N/A

### **Notes**

N/A