

PWR電源モジュールシリーズ

Moxaスイッチ用のホットスワップ対応の電源モジュール



機能と特長

- -40～85°Cの広範囲動作温度
- IEC 61850-3およびIEEE 1613準拠

認証



製品紹介

PWR電源モジュールシリーズのホットスワップ対応の電源モジュールは、Moxaスイッチ用に設計されています。電源モジュールにより、サポートされているスイッチは24/48 VDCまたは110/220 VAC/VDCを使用できます。

仕様

Power Parameters

Input Voltage	<p>PWR-HV-P48: 110/220 VDC/VAC for the switch system 48 VDC for PoE systems (53 to 57 VDC is recommended for PoE+ devices)</p> <p>PWR-LV-P48: 24/48 VDC for the switch system 48 VDC for PoE systems (53 to 57 VDC is recommended for PoE+ devices)</p> <p>PWR-HV-NP: 110/220 VDC/VAC for the switch system</p> <p>PWR-LV-NP: 24/48 VDC for the switch system</p>
Operating Voltage	<p>PWR-HV-P48: 88 to 300 VDC, 90 to 264 VAC for the switch system 46 to 57 VDC for PoE systems</p> <p>PWR-LV-P48: 18 to 72 VDC for the switch system 46 to 57 VDC for PoE systems</p> <p>PWR-HV-NP: 88 to 300 VDC, 90 to 264 VAC for the switch system</p> <p>PWR-LV-NP: 18 to 72 VDC for the switch system</p>
Reverse Polarity Protection	Supported
Alarm Contact Channels	1 relay output with current carrying capacity of 2 A @ 30 VDC or 0.5 A @ 125 VAC

Physical Characteristics

Weight	PWR-HV-P48: 360 g (0.79 lb) PWR-LV-P48: 360 g (0.79 lb) PWR-HV-NP: 340 g (0.75 lb) PWR-LV-NP: 340 g (0.75 lb)
--------	--

MTBF

Time	PWR-HV-P48: 1,530,831 hrs PWR-LV-P48: 1,388,747 hrs PWR-HV-NP: 2,556,214 hrs PWR-LV-NP: 2,710,293 hrs
Standards	Telcordia (Bellcore), GB

Warranty

Warranty Period	5 years
Details	See www.moxa.com/jp/warranty

注文情報

Model Name	Input Voltage	Operating Voltage	Supported Series
PWR-HV-P48	110/220 VDC/VAC 48 VDC for PoE systems	88-300 VDC, 90-264 VAC 46 to 57 VDC for PoE systems	PT-G7728 Series PT-G7828 Series MDS-G4012 Series MDS-G4020 Series MDS-G4028 Series MDS-G4012-L3 Series MDS-G4020-L3 Series MDS-G4028-L3 Series
PWR-HV-NP	110/220 VDC/VAC	88-300 VDC, 90-264 VAC	PT-G7728 Series PT-G7828 Series MDS-G4012 Series MDS-G4020 Series MDS-G4028 Series MDS-G4012-L3 Series MDS-G4020-L3 Series MDS-G4028-L3 Series MDS-G4012-4XGS Series MDS-G4020-4XGS Series MDS-G4028-4XGS Series MDS-G4012-L3-4XGS Series MDS-G4020-L3-4XGS Series MDS-G4028-L3-4XGS Series
PWR-LV-P48	24/48 VDC 48 VDC for PoE systems	18-72 VDC 46 to 57 VDC for PoE systems	PT-G7728 Series PT-G7828 Series MDS-G4012 Series MDS-G4020 Series MDS-G4028 Series MDS-G4012-L3 Series MDS-G4020-L3 Series MDS-G4028-L3 Series
PWR-LV-NP	24/48 VDC	18-72 VDC	PT-G7728 Series PT-G7828 Series MDS-G4012 Series MDS-G4020 Series MDS-G4028 Series MDS-G4012-L3 Series MDS-G4020-L3 Series MDS-G4028-L3 Series MDS-G4012-4XGS Series MDS-G4020-4XGS Series MDS-G4028-4XGS Series MDS-G4012-L3-4XGS Series MDS-G4020-L3-4XGS Series MDS-G4028-L3-4XGS Series

© Moxa Inc. All rights reserved. 2023年11月17日更新。

Moxa Inc.の明白な許可を書面で取得しない限り、本書およびその一部の複製や使用はいかなる方法やいかなる場合でも許可されません。製品の仕様は予告なく変更されることがあります。最新の製品情報については当社のWebサイトをご覧ください。