

UPort 1600-8-G2 シリーズ

8ポートRS-232/422/485 USB to シリアルコンバータ



機能とメリット

- USB 3.2 SuperSpeed 対応
- 512-byteのオンチップ FIFO キャッシュとフロー制御によりパフォーマンスを向上
- WindowsやLinuxを含む幅広いオペレーティングシステム用のドライバーを提供
- 50 bps ~ 921.6 kbpsのボーレート（非標準ボーレートをサポート）
- 両面LED設計により、前面と上面のどちらからでも電源、TX、RXのステータスを確認可能
- 追加の電源アダプタなしで最大32のシリアルポートをカスケード接続
- よりしっかりとした接続のためのラッチ付きUSBケーブル設計
- -40~75°C (-40~167°F) の環境に対しての広い動作温度モデルが利用可能
- 2 kV絶縁保護付きシリアルポート（「-I」モデル向け）

認証



製品紹介

UPort® 1600-8-G2シリーズのUSB to シリアルコンバータは、シリアルポート拡張が必要なノートパソコンやワークステーションコンピュータに最適です。現場でさまざまなシリアルデバイスを接続する必要があるコンピュータや、標準のCOMポートやDB9コネクタが無く、別途インターフェースコンバータを必要とするデバイスにとっては、この製品は不可欠です。UPortとコンピュータ間のより安全な接続のためのラッチやねじロックのあるUSBケーブルも付属しています。UPort® 1650-8-G2-Hubのカスケード機能を使用すると、電源アダプターをUPortに接続せずに最大32のシリアルポートを連結することができます。すべての製品は従来のシリアルデバイスと互換性があり、計測器やPOSアプリケーションで使用できます。

仕様

USB Interface

USB Standards	USB 1.1/2.0 compliant USB 3.2 Gen 2
Speed	5 Gbps, 480 Mbps, 12 Mbps
No. of USB Ports	1 x UFP for all models, and 3 additional DFP for UPort 1650-8-G2-Hub
USB Connector	USB type B (UFP) for all models, and type A (DFP) for UPort 1650-8-G2-Hub

Serial Interface

Connector	DB9 male
No. of Ports	8
Serial Standards	RS-232: UPort 1610-8-G2 RS-232/422/485: All other models
FIFO	512 bytes
Baudrate	50 bps to 921.6 kbps (supports non-standard baudrates)

Parity	None, Even, Odd, Space, Mark
Data Bits	5, 6, 7, 8
Stop Bits	1, 1.5, 2
Flow Control	RTS/CTS, XON/XOFF
RS-485 Data Direction Control	Automatic Data Direction Control (ADDC)
Pull High/Low Resistor for RS-485	1 kilo-ohm, 150 kilo-ohms
Terminator for RS-485	120 ohms
Surge	0.5 kV
Isolation	2 kV (I models)

Serial Signals

RS-232	TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND
RS-422	Tx+, Tx-, Rx+, Rx-, GND
RS-485-4w	Tx+, Tx-, Rx+, Rx-, GND
RS-485-2w	Data+, Data-, GND

Serial Software Features

Windows Drivers	Windows 11, 10, 8.1, 8, and 7 Windows Server 2022, 2019, 2016, 2012 R2, 2012 and 2008 R2
Linux Drivers	Kernel 6.x, 5.x and 4.x
Mac Drivers	macOS version (Intel 64): 13, 12, 11 and 10.1x
Virtual Machine	VMware Fusion (Windows on macOS 13, 12, 11, 10.1x, Intel 64) VMWare ESXi (Linux kernel 4) Parallels Desktop (Windows on macOS 13, 12, 11, 10.1x, Intel 64)
Arm®-based Platform Support	Linux kernel 6.x, 5.x and 4.x
Android API	Android 3.1.x and later

Power Parameters

Input Voltage	UPort 1610-8-G2/1650-8-G2 models: 5 VDC by USB bus power or 12 to 48 VDC by external power adaptor UPort 1650I-8-G2 models/1650-8-G2-Hub: 12 to 48 VDC by external power adaptor
Input Current	UPort 1610-8-G2: 308 mA @ USB 2.0, 495 mA @ USB 3.2, 260 mA @ 12 VDC UPort 1650-8-G2 models: 466 ma @ USB 2.0, 652 mA @ USB 3.2, 350 mA @ 12 VDC UPort 1650I-8-G2 models: 530 mA @ 12 VDC UPort 1650-8-G2-Hub: 2,250 mA @ 12 VDC
Output Power Rating	UPort 1650-8-G2-Hub: 900 mA @ 5 VDC (USB 3.2) 500 mA @ 5 VDC (USB 2.0)

Physical Characteristics

Housing	Metal
Dimensions	216 x 41.5 x 121.6 mm (8.50 x 1.63 x 4.79 in)

Weight	UPort 1610-8-G2: 650 g (1.43 lb) UPort 1650-8-G2 models: 670 g (1.48 lb) UPort 1650I-8-G2 models: 678 g (1.49 lb) UPort 1650-8-G2-Hub: 689 g (1.52 lb)
IP Rating	IP20

Environmental Limits

Operating Temperature	Standard models: 0 to 60°C (32 to 140°F) -T models: -40 to 75°C (-40 to 167°F)
Storage Temperature	-40 to 75°C (-40 to 167°F)
Ambient Relative Humidity	5 to 95% (non-condensing)

Standards and Certifications

EMC	EN 55032/35
EMI	CISPR 32, FCC Part 15B Class A
EMS	IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m IEC 61000-4-4 EFT: Power: 1 kV IEC 61000-4-5 Surge: Power: 1 kV, Signal: 0.5 kV IEC 61000-4-6 CS: 3 V; 150 kHz to 80 MHz IEC 61000-4-8 PFMF
Safety	IEC 62368-1 EN 62368-1 UL 62368-1 (CB) KC
Green Product	RoHS, CRoHS, WEEE
Vibration	IEC 60068-2-6 IEC 60068-2-64
Shock	IEC 60068-2-27
Freefall	IEC 60068-2-31

MTBF

Standards	Telcordia Standard SR332, Telcordia Issue 2
Time	UPort 1610-8-G2: 1,431,860 hrs UPort 1650-8-G2 models: 951,145 hrs UPort 1650I-8-G2 models: 782,795 hrs UPort 1650-8-G2-Hub: 823,983 hrs

Package Contents


Device	1 x UPort 1600-8-G2
Cable	1 x USB 3.2 Gen 1 cable with latch and screw
Installation Kit	4 x rubber stand
Documentation	1 x quick installation guide 1 x warranty card
Power Supply	Power adapter, suitable for your region (UPort 1650I-8-G2 and UPort 1650-8-G2- Hub only)

Warranty

Warranty Period	5 years Note: Product only
Details	See www.moxa.com/warranty

寸法

単位：mm（インチ）



注文情報

Model Name	Serial Standards	No. of Serial Ports	Isolation	Power Input	Operating Temp.
UPort 1610-8-G2	RS-232	8	-	USB bus power/ Power adapter	0 to 60°C
UPort 1650-8-G2	RS-232/422/485	8	-	USB bus power/ Power adapter	0 to 60°C
UPort 1650-8-G2-T	RS-232/422/485	8	-	USB bus power/ Power adapter	-40 to 75°C
UPort 1650I-8-G2	RS-232/422/485	8	2 kV	Power adapter	0 to 60°C
UPort 1650I-8-G2-T	RS-232/422/485	8	2 kV	Power adapter	-40 to 75°C
UPort 1650-8-G2-Hub	RS-232/422/485	8	-	Power adapter	0 to 60°C

アクセサリ

Cables

CBL-USB3-BA-G-120	USB 3.2 Gen 1 cable, type A-to-type B with latch and screw, 1.2 m
CBL-USB3-BA-G-028	USB 3.2 Gen 1 cable, type A-to-type B with latch and screw, 0.28 m
CBL-USB3-BA-BK-120	USB 3.2 Gen 1 cable, type A-to-type B, 1.2 m
CBL-F9M9-20	DB9 female to DB9 male serial cable, 20 cm
CBL-F9M9-150	DB9 female to DB9 male serial cable, 1.5 m

Connectors

LB-DB9F-G-01	Serial loopback DB9 adaptor
Mini DB9F-to-TB	DB9 female to terminal block connector
ADP-RJ458P-DB9F	DB9 female to RJ45 connector
A-ADP-RJ458P-DB9F-ABC01	DB9 female to RJ45 connector for the ABC-01 Series

Wall-Mounting Kits

WK-UP400A-BOT-BK	Bottom-panel wall-mounting kit for the UPort 400A/1400-G2/1600-G2 Series with 2 plates (43 x 30 x 2 mm or 1.69 x 1.18 x 0.08 in), 6 M3 x 5 mm screws
------------------	--

DIN-Rail Mounting Kits

DK-UP1600-G2	DIN Rail mounting kits for UPort 1600-G2
--------------	--

Rack-Mounting Kits

RK-UP1600-G2	Rack mounting kits for UPort 1400/1600-G2
--------------	---

Power Adapters

PWR-12050-EU-S1	Locking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, EU plug, 0 to 40°C operating temperature Applicable Models: UPort 1610-8-G2 UPort 1650-8-G2 UPort 1650I-8-G2
PWR-12050-USJP-S1	Locking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, US/JP plug, 0 to 40°C operating temperature Applicable Models: UPort 1610-8-G2 UPort 1650-8-G2 UPort 1650I-8-G2
PWR-12050-CN-S1	Locking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, CN plug, 0 to 40°C operating temperature Applicable Models: UPort 1610-8-G2 UPort 1650-8-G2 UPort 1650I-8-G2
PWR-12050-UK-S1	Locking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, UK plug, 0 to 40°C operating temperature Applicable Models: UPort 1610-8-G2 UPort 1650-8-G2 UPort 1650I-8-G2
PWR-12050-AU-S1	Locking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, AU plug, 0 to 40°C operating temperature Applicable Models: UPort 1610-8-G2 UPort 1650-8-G2 UPort 1650I-8-G2
PWR-12050-KR-S1	Locking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, KR plug, 0 to 40°C operating temperature Applicable Models: UPort 1610-8-G2/KC UPort 1650-8-G2/KC UPort 1650I-8-G2/KC
PWR-12300-WP-S2	Locking barrel plug with 12 VDC, 3 A, 100 to 240 VAC, without plug, 0 to 40°C operating temperature Applicable Models: UPort 1650-8-G2-Hub UPort 1650-8-G2-Hub/KC
PWR-Plug-EU-02	EU plug for PWR-12150-WPEU and PWR-12300-WPEU Applicable Models: UPort 1650-8-G2-Hub
PWR-Plug-USJP-02	US/JP plug for PWR-12150-WPUSJP and PWR-12300-WPUSJP

	Applicable Models: UPort 1650-8-G2-Hub
PWR-Plug-CN-02	CN plug for PWR-12150-WPCN and PWR-12300-WPCN Applicable Models: UPort 1650-8-G2-Hub
PWR-Plug-UK-02	UK plug for PWR-12150-WPUK and PWR-12300-WPUK Applicable Models: UPort 1650-8-G2-Hub
PWR-Plug-AU-03	AU plug for PWR-12300-WPAU Applicable Models: UPort 1650-8-G2-Hub
PWR-Plug-KR-02	KR plug for the PWR-12150-WPKR and the PWR-12300-WPKR Applicable Models: UPort 1650-8-G2-Hub/KC
PWR-12150-EU-SA-T	Locking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, EU plug, -40 to 75°C operating temperature Applicable Models: UPort 1650-8-G2-T UPort 1650I-8-G2-T
PWR-12150-USJP-SA-T	Locking barrel plug, 12 VDC 1.5 A, 100 to 240 VAC, US/JP plug, -40 to 75°C operating temperature Applicable Models: UPort 1650-8-G2-T UPort 1650I-8-G2-T
PWR-12150-CN-SA-T	Locking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, CN plug, -40 to 75°C operating temperature Applicable Models: UPort 1650-8-G2-T UPort 1650I-8-G2-T
PWR-12150-UK-SA-T	Locking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, UK plug, -40 to 75°C operating temperature Applicable Models: UPort 1650-8-G2-T UPort 1650I-8-G2-T
PWR-12150-AU-SA-T	Locking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, AU plug, -40 to 75°C operating temperature Applicable Models: UPort 1650-8-G2-T UPort 1650I-8-G2-T

© Moxa Inc. All rights reserved.2023年10月16日更新。

Moxa Inc.の明白な許可を画面で取得しない限り、本書およびその一部の複製や使用はいかなる方法やいかなる場合でも許可されません。製品の仕様は予告なく変更されることがあります。最新の製品情報については当社のWebサイトをご覧ください。