

Transio A52/A53 Series

Entry-level RS-232 to RS-422/485 converters



Features and Benefits

- ADDC™ (Automatic Data Direction Control) RS-485 data control
- Automatic baudrate detection
- RS-422 hardware flow control: CTS, RTS signals
- LED indicators for power and signal status
- RS-485 multidrop operation, up to 32 nodes
- 2 kV isolation protection (A53)
- Built-in 120-ohm termination resistors

Certifications



Introduction

The A52 and A53 are general RS-232 to RS-422/485 converters designed for users who need to extend RS-232 transmission distance and increase networking capability.

Specifications

Serial Interface

Connector	10-pin RJ45
Flow Control	RTS/CTS
Isolation	A53 Series: 2 kV
No. of Ports	2
RS-485 Data Direction Control	ADDC® (automatic data direction control)
Serial Standards	RS-232, RS-422, RS-485

Serial Signals

RS-232	TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND
RS-422	Tx+, Tx-, Rx+, Rx-, RTS+, RTS-, CTS+, CTS-, GND
RS-485-4w	Tx+, Tx-, Rx+, Rx-, GND
RS-485-2w	Data+, Data-, GND

Power Parameters

Input Current	A52 Series: 170 mA @ 9 VDC A53 Series: 195 mA @ 9 VDC
Input Voltage	9 to 30 VDC
No. of Power Inputs	1
Overload Current Protection	Supported

Power Consumption	A52 Series: 170 mA @ 9 VDC A53 Series: 195 mA @ 9 VDC
Source of Input Power	Power input jack
Physical Characteristics	
Housing	Plastic
IP Rating	IP30
Dimensions	90 x 60 x 21 mm (3.54 x 2.36 x 0.83 in)
Weight	85 g (0.19 lb)
Installation	Desktop
Environmental Limits	
Operating Temperature	0 to 55°C (32 to 131°F)
Storage Temperature (package included)	-20 to 75°C (-4 to 167°F)
Ambient Relative Humidity	5 to 95% (non-condensing)
Standards and Certifications	
EMC	EN 55032/24
EMI	CISPR 32, FCC Part 15B Class A
EMS	IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m IEC 61000-4-4 EFT: Power: 1 kV; Signal: 0.5 kV IEC 61000-4-5 Surge: Power: 1 kV IEC 61000-4-6 CS: 150 kHz to 80 MHz: 3 V/m; Signal: 3 V/m IEC 61000-4-8 PFMF
Environmental Testing	IEC 60068-2-1 IEC 60068-2-14 IEC 60068-2-2 IEC 60068-2-3
Safety	EN 60950-1, IEC 60950-1
Vibration	IEC 60068-2-6
MTBF	
Time	1,870,854 hrs
Standards	Telcordia (Bellcore), GB
Warranty	
Warranty Period	5 years
Details	See www.moxa.com/warranty
Package Contents	
Device	1 x Transio A52/A53 Series converter
Cable	1 x 10-pin RJ45 to DB9F (-DB9F models) 1 x 10-pin RJ45 to DB25F (-DB25F models)
Documentation	1 x quick installation guide 1 x warranty card

Ordering Information

Model Name	Serial Isolation	Power Adapter Included	Serial Cable
A52-DB9F w/o Adapter	-	-	DB9F
A52-DB25F w/o Adapter	-	-	DB25F
A52-DB9F w/ Adapter	-	✓	DB9F
A52-DB25F w/ Adapter	-	✓	DB25F
A53-DB9F w/o Adapter	✓	-	DB9F
A53-DB25F w/o Adapter	✓	-	DB25F
A53-DB9F w/ Adapter	✓	✓	DB9F
A53-DB25F w/ Adapter	✓	✓	DB25F

© Moxa Inc. All rights reserved. Updated Nov 12, 2018.

This document and any portion thereof may not be reproduced or used in any manner whatsoever without the express written permission of Moxa Inc. Product specifications subject to change without notice. Visit our website for the most up-to-date product information.